

## 52" FIBERGLASS BELT DRIVE EXHAUST FAN

FFM523G1-3V

### Product Description

Schaefer fiberglass exhaust fans are designed and built to be highly efficient (high cfm/watt), long lived and competitively priced fans for agricultural and other applications. The fiberglass exhaust fans are used worldwide to exhaust high volumes of air from factories, warehouses, garages and other locations, where building owners value low capital cost and low operating cost. Fans ship fully assembled with aluminum inlet shutters, self-adjusting belt tensioner and powder coated outlet guard.

### Features

Totally enclosed, thermally protected motors for safety and long life

Easy belt replacement, minimal maintenance required

Remote Lubrication System optional

Aluminum inlet shutter and powder coated outlet guard

Suitable for buildings with up to 12" wall thickness

Available in 36", 48" and 52" sizes

1-phase and 3-phase motors of various sizes

15 year housing warranty

Two year warranty

Made in the USA



### Specifications

<b>Blade Color</b>	Gray
<b>Brand</b>	Schaefer
<b>Cfm (free Air)</b>	TBD
<b>Drive</b>	Belt
<b>Housing Material</b>	Fiberglass
<b>Phase</b>	3
<b>Rough-in Dimensions</b>	59 1/4" x 59 1/4"
<b>Speeds</b>	1
<b>Vfd Compatible</b>	Yes
<b>Cfm/watt (free Air)</b>	TBD
<b>Cord</b>	Not included

<b>Guard Color</b>	Black
<b>Nameplate Amps</b>	3.2/1.6
<b>Number Of Wings</b>	3
<b>Power (hp)</b>	1
<b>Product Dimensions (L X W X H Inches)</b>	TBD
<b>Product Net Weight (lbs)</b>	TBD
<b>Voltage</b>	208-230/460
<b>Air Velocity (@ 5 Times Diameter)</b>	TBD
<b>Blade Material</b>	Galvanized Steel

<b>Fixed Or Portable</b>	Fixed
<b>Guard Material</b>	Powder Coated Steel
<b>Oscillating</b>	No
<b>Country Of Origin</b>	US
<b>Guard Spacing (inches)</b>	1 - 2
<b>Housing Color</b>	White
<b>Cfm/watt (@0.10")</b>	TBD
<b>Maximum Static Pressure (in. H2o)</b>	TBD
<b>Cfm (@ 0.10")</b>	TBD

<b>Diameter (inches)</b>	52
<b>Frequency (hz)</b>	60/50

<b>Cfm (high)</b>	TBD
<b>Product Color</b>	White
<b>Speed Control Compatible?</b>	No
<b>Cfm Range (free Air)</b>	TBD

<b>Cfm/watt (@0.05")</b>	TBD
<b>Cfm (@0.05")</b>	24060